

ASSEMBLY INSTRUCTIONS for E12 DELUXE HEADGEAR SYSTEM

ATTACHING 8170 POLYCARBONATE FACE SHIELD TO HOOD

With the bottom of the Face Shield pulled inward toward the ratchet, push each notched end of the Face Shield into the slots in the Hood Crown that are nearest to the tension Knobs (Figure 1). Push the top of the Face Shield toward the hood into position (Figure 2), making sure the Release Tab in the center of the top edge of the Hood goes inside the slot in the Face Shield (Figure 3) and locks into place.




Figure 1



Figure 2




Figure 3

DETACHING FACE SHIELD FROM HOOD

Find the Release Tab for the Face Shield at the center slot in the Hood and press firmly to release the catch (Figure 4). Pull the bottom of the Face Shield away from Hood (Figure 5) and lift the Face Shield out of the slot in the Hood Crown (Figure 6).




Figure 4



Figure 5



Figure 6

RATCHET ADJUSTMENT

To adjust the headband, push in and turn the ratchet knob to the desired size then release.

HEIGHT ADJUSTMENT

To adjust the height of the headgear on head, change the position of the pin-lock on the top band, increasing the length of the band to lower the headgear or decreasing the length to raise the headgear.

SHIELD ANGLE ADJUSTMENT

The shield angle can be adjusted by loosening the side knobs and changing the pin position to one of the four pin holes located at the temples of the adjustment bracket.